



## 38 HAA

Tested according EN 12825

### General characteristics

Measurements	600 x 600 mm
Weight	+/- 10,2 kg
Core	38 mm chipboard - density 720 kg/m <sup>3</sup> - E1
Bottom side	aluminium foil 0,05 mm
Top side	aluminium foil 0,05 mm
Edge banding	PVC/ABS 0,6 mm

### System characteristics

Class of element	1
Ultimate load	>=4kN
Safety factor	2
Point load	2kN
Class of deflection (max. 2,5 mm deflection by 2kN)	A
Divided load per m <sup>2</sup> (theoretical value)	10kN-15kN / m <sup>2</sup>

### Fire characteristics

Fire resistance	F30 according DIN 4102-2/REI30 according EN13501-2
Fire reaction	class B2 according DIN 4102-1

### Electrical characteristics

Electrical resistance	>=10 <sup>9</sup> Ohm
Other values are possible when using conductive edge banding and conductive glue.	

Complete certificates on request

Jansen Products NV  
Fabriekstraat 4  
3670 Meeuwen  
BELGIUM

Tel : +32 11 79 33 00  
Fax : +32 11 79 33 01  
[Info@jansenproducts.be](mailto:Info@jansenproducts.be)  
[www.groupjansen.com](http://www.groupjansen.com)

 **JANSEN**  
products